



100% VISCOSE RAYON BROIDERY THREAD

## Duravis®

DURAK Duravis® is a high quality continuous filament viscose rayon broidery thread specially produced for broidery machines. It provides excellent performance even on high speed broidery machines. Thanks to its natural structure, it gives a soft touch feeling where the embroidery touches the skin. It provides vivid and brilliant appearance. DURAK Duravis® appeals to a wide range of applications in conjunction with its bright and ample colors, thickness options and excellent broidery performance.



### Areas of Use

- Broidery
- Apparel
- Underwear
- Home Textile

### Product Properties

- Reliable and soft embroidery thread with natural appearance.
- High color fastness.
- Vivid and brilliant appearance.
- Offers feel and texture similar to natural fibers.
- Works extremely smoothly.

# Duravis®

## Storage Conditions

Must be stored away from heat, humidity and direct sunlight.

## Points to consider

**Embroidered products made with Viscose can be washed, boiled and have light fastness. However, in order to protect the color fastness of the embroidery, the following points should be taken into consideration during washing.**

- 1- Embroidered items should be washed separately and not washed with other products.
- 2- It should not be placed in the washing machine tightly, because the movement of the embroidered items inside the tub should be easy.
- 3- Embroidery products should be shaken immediately after washing, and should not be left folded or stacked when wet and damp.
- 4- Embroidered items (that do not contain chemical mixtures) should be washed with mild detergents. Heavy chemicals and bleach can cause embroidery discoloration.
- 5- Embroideries on woolen fabrics should not be washing in the machine and should not be shaken.
- 6- Stain remover or whitening products should not be used to remove stains.
- 7- Embroideries made of Viscose, can be applied with dry cleaning.
- 8- Ironing should be done on the reverse of the embroidered surface or on another fabric. During ironing, the lowest possible temperature and a steam iron should be used instead of a moist cloth.
- 9- Due to environmental reasons applied for the protection of nature, we have to change some materials used in paint and painting periodically. Therefore, despite all our efforts, there may be some slight differences between the color chart and the product.

## Thickness and Strength Chart

Ticket No.	Nominal Tex	Strength CN	Elongation %	Needle Size (Nm)
50/1*2	10	300	15 - 20	*
80/1*2	16	360	15 - 20	*
120/1*2	24	620	15 - 20	*

## Color Fastness

Washing fastness at 60°C	ISO 105 C06	Min. 4
Water fastness	ISO 105 E01	Min. 4
Friction fastness	ISO 105 X12	Min. 4
Dry cleaning fastness	ISO 105 D01	Min. 4
Perspiration fastness	ISO 105 E04	Min. 4

## Presentation

Durak Duravis® offers a wide range of colors in a variety of meters size and thicknesses.

